











Atoka® ANSI • CSA •



RUBBER
TIPS

Integrated nosepiece // Soft non-slip rubber temple tips provide non-binding fit

Lens and Temples | 8 Variations

| | | |
|---|------------|---------------|
|  | S9110S •• | Clear |
|  | S9110ST •• | Clear AF |
|  | S9120S •• | Gray |
|  | S9120ST •• | Gray AF |
|  | S9130S •• | Amber |
|  | S9160S •• | Infinity Blue |
|  | S9180S •• | I/O Mirror |
|  | S9180ST •• | I/O Mirror AF |

General Specifications

Weight: 22.2 gm
 Bridge: 12.7 mm
 Lens base: 10 curve
 Lens size diagonal: 79 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 157 mm
 Overall width (hinge - hinge): 137mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple Tip: polyvinyl chloride (PVC)
 Nosepiece: polycarbonate
 Hinge: polycarbonate

| Part No. | Lens Marking | Temple Marking |
|----------|-----------------|------------------------------------|
| S9110S | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9110ST | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9120S | P Z87 + U6 L2.5 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9120ST | P Z87 + U6 L2.5 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9130S | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9160S | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9180S | P Z87 + U6 L1.7 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| S9180ST | P Z87 + U6 L1.7 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices