

EMERGE®

Stylish Dual Frame With Full Eye Protection



Black Frame

Part	Lens
SB7910DRX ●●●	<input type="checkbox"/> Clear
SB7910D15 ●●	<input type="checkbox"/> Clear +1.5
SB7910D20 ●●	<input type="checkbox"/> Clear +2.0

Translucent Gray Frame

Part	Lens
SG7910DRX ●●●	<input type="checkbox"/> Clear
SG7910D15 ●●	<input type="checkbox"/> Clear +1.5
SG7910D20 ●●	<input type="checkbox"/> Clear +2.0

- Suitable for both working environments and sports activities.
- Soft nose piece provides comfort for extended use without slipping.
- Stylish dual lens with full eye protection, plano lens, prescription lens, and full reader lens adaptable.
- Will accommodate an Rx lens to the maximum of +3 to -3 diopters.

GENERAL SPECIFICATION

Bridge: 13mm
Closest Point Between Lens: 17.7mm
Closest Point Between Temple Tips: 83mm
Lens Base: 6 Curve
Lens Size Diagonal: 58mm
Lens Size Vertical: 42.5mm
Lens Thickness: 2.2mm
Overall Length [Lens-Tip]: 163mm
Overall Width [Hinge-Hinge]: 135mm
PD: 68mm
Weight: 30gm

EMERGE®

Stylish Dual Frame With Full Eye Protection







PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 base curve, dual lens frame style
Frame	G300 Nylon	Wrap around design with wide temples for extended side protection
Nose piece	PVC	Glued onto the nose bridge, pillow softness
Temple	Polycarbonate	Spatula Type
Hinge	Polycarbonate	3 barrel type, integral to frame/temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB7910DRX	 Clear	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB7910D15	 Clear +1.5	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB7910D20	 Clear +2.0	2 C - 1.2 P 1 F CE	CE P EN166 F
ESG7910DRX	 Clear	2 C - 1.2 P 1 F CE	CE P EN166 F
ESG7910D15	 Clear +1.5	2 C - 1.2 P 1 F CE	CE P EN166 F
ESG7910D20	 Clear +2.0	2 C - 1.2 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust