




Ridgeline® / Ever-Lite / RVZ2620


















Ever-Lite® ANSI • CE • CSA •



Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm

Black Frame | 15 Variations

 SB8610D ●●● Clear	 SB8625DTM ●● Light Gray H2MAX AF
 SB8610DT ●●● Clear H2X AF	 SB8630D ●●● Amber
 SB8610DTM ●●● Clear H2MAX AF	 SB8660D ●● Infinity Blue
 SB8620D ●●● Gray	 SB8660DTM ●● Infinity Blue H2MAX AF
 SB8620DT ●●● Gray H2X AF	 SB8665D ●● Ice Blue Mirror
 SB8620DTM ●●● Gray H2MAX AF	 SB8680D ●●● I/O Mirror
 SB8623D ●● Dark Gray	 SB8680DT ●●● I/O Mirror AF
 SB8624D ●●● Photochromic	



WATCH THE VIDEO








Vimeo.com/Pyramex/H2MAX

i Photochromic lens changes from clear to dark, after exposed to direct UV light. Changes from dark to clear, after removed from UV light.

Ever-Lite® Readers ANSI • CSA •

Soft nosepiece for snug fit // Slim co-injected temples // Lightweight spectacle – 22 gm

Black Frame | 7 Variations

 SB8610R15 ●● Clear	+1.5 Mag
 SB8610R20 ●● Clear	+2.0 Mag
 SB8610R25 ●● Clear	+2.5 Mag
 SB8610R30 ●● Clear	+3.0 Mag
 SB8620R15 ●● Gray	+1.5 Mag
 SB8620R20 ●● Gray	+2.0 Mag
 SB8620R25 ●● Gray	+2.5 Mag



Ever-Lite®

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8610DT	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8610DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620DTM	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8623D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8624D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8630D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8660D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8665D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8680D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

Ever-Lite Readers

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB8610R15	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R20	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R25	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R30	P + U6	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R15	P + U6 L2.5	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R20	P + U6 L2.5	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R25	P + U6 L2.5	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L2.5: 29% max visible light

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 +3.00: magnification of +3.0
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices