

FORUM®

Fashionable Stream Line Design



Black Frame

Part	Lens
ESB6610D •••	<input type="checkbox"/> Clear
ESB6610DT ••••	<input type="checkbox"/> Clear H2X Anti-Fog
ESB6620D •••	<input type="checkbox"/> Gray
ESB6680D •••	<input type="checkbox"/> Indoor/Outdoor Mirror

- Soft PVC nose piece generates a cushion for a comfort fit.
- Metal emblem on temple presents this premium eyewear at the top of its class.
- Fashionable stream line design incorporates the elements of safety in trend setting eyewear.
- 9.5 base curve lens provides excellent side protection, scratch-resistant polycarbonate provides 99.9% UV protection.





GENERAL SPECIFICATION

Bridge: 12.4mm
Closest Point Between Lens: 11.6mm
Closest Point Between Temple Tips: 86mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 80mm
Lens Size Vertical: 45mm
Lens Thickness: 2.3mm
Overall Length [Lens-Tip]: 159mm
Overall Width: 138mm
PD: 68mm
Weight: 26gm

PACKAGING

Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Nose Piece	PVC	Universal fit
Frame	Polycarbonate	Lens clipped to frame
Emblem	Red Bronze	Attached to the temple
Screw	Stainless Steel	Standard hinge screw
Hinge	Polycarbonate	3 barrel type
Lens	Polycarbonate	9.5 base wrap around lens
Temple	Polycarbonate	Straight side sports style

PART	LENS	LENS MARKING	FRAME MARKING
ESB6610D	 Clear	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB6610DT	 Clear H2X Anti-Fog	2 C - 1.2 P 1 FN CE	CE P EN166 F
ESB6620D	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB6680D	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust