



GL501C5 Series

Crinkle Latex Gloves

GL501C5 Series **ANSI CE**

13 gauge cut-resistant HPPE liner

Tear and abrasion resistant

High elasticity and grip

Crinkle latex palm suited for wet and dry conditions

Flexible and durable over a wide range of temperatures

Part No.	Sizes
EGL501C5 ●●	S, M, L, XL, 2XL

Sizing

The color of the binding around the cuff indicates the glove size.

■ Small (7) <i>Red</i>	■ Medium (8) <i>Yellow</i>	■ Large (9) <i>Brown</i>	■ X-Large (10) <i>Black</i>	■ 2X-Large (11) <i>Blue</i>
------------------------------------------------------------	-------------------------------------------------------------------	----------------------------------------------------------------	-------------------------------------------------------------------	------------------------------------------------------------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Materials

Coating: Crinkle latex

Liner shell: 13 gauge HPPE

Cuff: HPPE & latex elastic

Country of Origin: China

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex

Cleaning

Wash in warm water (30-40°C) (86-104°F)

Use mild detergent

Short cycle time (5-10 minutes)

Low Tumble dry (60°C max) (140°F max)

Do not use any chemicals or sharp-edged objects for cleaning the gloves. Cleaning can alter the performance levels of the glove.

There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com



EN388

3542



Cat. II

1,544 g



Abrasion Rated	Circular Blade Cut Rated	Tear Rated	Puncture Rated
1-4	1-5	1-4	1-4

Standards

CE EN388 standard features abrasion, cut, tear and puncture ratings. Abrasion ratings are based on the number of cycles required to abrade through the sample glove. Cut ratings are based on the number of cycles required to cut through the sample at a constant speed. Tear ratings are based on the amount of force required to tear the sample. Puncture ratings are based on the amount of force required to pierce the sample with a standard-sized point.

ANSI standard features cut ratings that range from A1 through A9. Cut ratings are based on the grams of weight needed to cut through the material. Our ANSI cut level glove options include A2 (500-999 grams to cut), A3 (1,000-1,499 grams to cut) and A4 (1,500-2,199 grams to cut).

Testing Performance

EN388: 2003

Abrasion (6,633)	1	2	3	4	
Cut	1	2	3	4	5
Tear	1	2	3	4	
Puncture	1	2	3	4	

ANSI/ISEA 105-2016

Cut	1	2	3	4	5
-----	---	---	---	---	---

Gloves meet European EN388:2003 (●) standards. Some meet ANSI/ISEA 105-2016 (●) standards. Gloves are sold by the dozen only. For specific options visit our website or contact your sales representative.