

Montello®

Sporty Frame Design



Black Frame


Part

VGSB618TB•••

VGSB622TB•••

VGSB670TB••

Lens

 Bronze H2X Anti-Fog

 Forest Gray H2X Anti-Fog

 Silver Mirror Anti-Fog




- Full frame, dual lens design.
- Durable, flexible nylon frame and temples.
- Built-in nosepiece.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION

Bridge: 12.5mm
Closest Point Between Lens: 18.6mm
Closest Point Between Temple Tips: 95mm
Lens Base: 8 Curve
Lens Size Diagonal: 64mm
Lens Size Vertical: 43mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 161mm
Overall Width (Hinge-Hinge): 129.5mm
Weight: 32gm
PD: 64mm

PACKAGING
Static sticker on bottom left lens
Temple tag with UPC code label
Sold individually in Venture Gear branded polybag
Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base wrap around lens
Frame	Nylon	Dual frame with side protection
Temple	Nylon	Spatula
Nose Piece	Nylon	Integral to frame
Screw	Stainless Steel	Standard Hinge Screw
Hinge	Nylon	3 barrel type, integral to frame/temple
Metal emblem	Copper	Attached on the temple

PART	LENS	LENS MARKING	FRAME MARKING
VGSB618TB	 Bronze H2X Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB622TB	 Forest Gray H2X Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB670TB	 Silver Mirror Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices