

Onix® ANSI • CE • AS • Ballistic •



CO-INJECTED
TEMPLES



ADJUSTABLE
NOSEPIECE



RATCHETING
TEMPLES

Ratcheting co-injected temples // Adjustable rubber nosepiece // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Black Frame | 5 Variations

| | | |
|--|----------------|---------------------|
| | SB4910S ●●● | Clear |
| | PYSB4910S* ●●● | Clear |
| | SB4910ST ●●● | Clear H2X AF |
| | SB4920S ●●● | Gray |
| | SB4980S ●●● | I/O Mirror |

Black and Green Frame | 1 Variation

| | | |
|--|--------------|---------------------|
| | SGR4910ST ●● | Clear H2X AF |
|--|--------------|---------------------|



SGR49

Black and Pink Frame | 2 Variations

| | | |
|--|---------------|-------|
| | SP4910S ●● | Clear |
| | PYSP4910S* ●● | Clear |



SP49



*Pyramex retail packaged product

General Specifications

Weight: 27 gm
 Bridge: 15 mm
 Lens base: 8 curve
 Lens size diagonal: 141 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 161 mm
 Overall width (hinge - hinge): 128mm
 Closest point between temple tips: 68 mm

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Nosepiece: polycarbonate | Nosepad: TPE
 Screw: Stainless Steel
 Ratchets: Nylon
 Side Shields: polycarbonate

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

| Part No. | Lens Marking | Frame Marking |
|------------|-----------------|---------------|
| SB4910S | P Z87 + U6 | P Z87 + |
| PYSB4910S* | P Z87 + U6 | P Z87 + |
| SB4910ST | P Z87 + U6 | P Z87 + |
| SB4920S | P Z87 + U6 L2.5 | P Z87 + |
| SB4980S | P Z87 + U6 L1.7 | P Z87 + |
| SGR4910ST | P Z87 + U6 | P Z87 + |
| SP4910S | P Z87 + U6 | P Z87 + |
| PYSP4910S* | P Z87 + U6 | P Z87 + |

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards [●] and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] [●] Canadian [CSA Z94.3-15 [●] third-party certification] [●], or Ballistic [MIL-PRF-32432] [●] standards.