


Atwater™ **ANSI CSA**


Soft, rubber nosepiece

Wide straightback temples

Part No.	Black Frame
VGSB1226TB ●●	AF Forest Gray H2X
VGSB1265TB ●●	AF Ice Blue Mirror
Part No.	Black and Silver Frame
VGSSB1226TB ●●	AF Forest Gray H2X
VGSSB1265TB ●●	AF Ice Blue Mirror



There's more to see at
VENTUREGEAR.COM
 (P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and Canadian (CSA Z94.3) (●) standards. All lenses are hard coated polycarbonate scratch-resistant and provide 99% protection from harmful UV rays.

Atwater™

General Specifications

Weight: 30.3 gm
 Lens base: 9 curve
 Lens thickness: 2.2 mm
 Bridge: 12.8 mm
 Lens size vertical: 43.3 mm
 Lens size diagonal: 76.4 mm
 Overall length (lens - tip): 169 mm
 Overall width (hinge - hinge): 138.8 mm
 Closest point between temple tips: 97 mm
 Closest point between lens: 14.2 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Frame: polycarbonate
 Nose piece: thermoplastic rubbers (TPR)
 Screw: stainless steel
 Hinge: polycarbonate

Part No.	Lens Marking	Temple Marking
VGSB1226TB	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
VGSB1265TB	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
VGSSB1226TB	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
VGSSB1265TB	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

