










Black Frame

- | Part | Lens |
|-------------|--------------------------------------------------------------------------------------------------------------|
| VGSB922T •• |  Forest Gray Anti-Fog |
| VGSB965T •• |  Ice Blue Mirror Anti-Fog |
| VGSB931 ••• |  Polarized Green Mirror |

White Frame

- | Part | Lens |
|-------------|----------------------------------------------------------------------------------------------------------------|
| VGSW922T •• |  Forest Gray Anti-Fog |
| VGSW965T •• |  Ice Blue Mirror Anti-Fog |
| VGSW931 ••• |  Polarized Green Mirror |

Tortoise Frame

- | Part | Lens |
|-------------|-----------------------------------------------------------------------------------------------------|
| VGST918T •• |  Bronze Anti-Fog |

Clear Frame

- | Part | Lens |
|-------------|----------------------------------------------------------------------------------------------------------------|
| VGSC965T •• |  Ice Blue Mirror Anti-Fog |









- Built-in rubber nosepiece.
- Stylish full-frame high performance eyewear.
- Vented frame increases air flow to prevent fogging.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION

Bridge: 13.5mm
Lens Base: 8 Curve
Lens Size Diagonal: 62mm
Lens Size Vertical: 42.8mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 160mm
Overall Width (Hinge-Hinge): 132.6mm
Weight: 31.7gm
PD: 64mm
Closest point between lenses: 18.9mm
Closest point between temple tips: 86mm

PACKAGING
Static sticker on bottom left lens
Temple sticker hanging from left temple
Each glass placed into color box + UPC code label
Sold individually in Venture Gear branded box
Case: 60 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection - 8 base dual lens
Frame	Polycarbonate	Over-molding frame with rubber brow bar
	TPE	
Nose Piece	TPE	Integral to frame
Temple	Polycarbonate	Curved spatula temple
Metal Emblem	Copper	Recessed on temples
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB922T	 Forest Gray Anti-Fog	P + S	P Z87 +
VGSB965T	 Ice Blue Mirror Anti-Fog	P + S	P Z87 +
VGSB931	 Polarized Green Mirror	P + S	P Z87 +
VGSC965T	 Ice Blue Mirror Anti-Fog	P + S	P Z87 +
VGST918T	 Bronze Anti-Fog	P + S	P Z87 +
VGSW922T	 Forest Gray Anti-Fog	P + S	P Z87 +
VGSW965T	 Ice Blue Mirror Anti-Fog	P + S	P Z87 +
VGSW931	 Polarized Green Mirror	P + S	P Z87 +

LENS MARKING

Symbols:

- P: Manufacturer's mark
- Z87: ANSI standard for Eye and Face protection devices
- +: High Impact
- H: Small Head Size
- S: Special Purpose

UV Filter Transmittance:

- U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
- U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
- U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
- U4: Max Effective Far UV= .04% / Max Near UV= .5%
- U5: Max Effective Far UV= .02% / Max Near UV= .2%
- U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

- L1.3: 85% Max. Visible Light
- L1.7: 55% Max. Visible Light
- L2.5: 29% Max. Visible Light
- L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

- P: Manufacturer's mark
- Z87: ANSI standard for Eye and Face protection devices
- +: High Impact
- P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices