



Venture 3® ANSI CE CSA AS BALLISTIC



VENTED
FRAME



ADJUSTABLE
NOSEPIECE



ADJUSTABLE
TEMPLES



CO-INJECTED
TEMPLES

Soft, adjustable nosepiece

Ventilated frame

Adjustable co-injected rubber temples

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Part No.	Black Frame
SB5710D ●●●●	Clear
PYSB5710D* ●●●●	Clear
SB5710DT ●●●●	AF Clear H2X
SB5710DTM ●●●●	AF Clear H2MAX
SB5720D ●●●●	Gray
SB5720DT ●●●●	AF Gray H2X
SB5730D ●●●●	Amber
PYSB5730D* ●●●●	Amber
SB5750SFT ●	AF 5.0 IR Filter H2X
SB5760D ●●●●	Infinity Blue
SB5760SFT ●	AF 3.0 IR Filter H2X
SB5770D ●●●●	Silver Mirror
SB5780D ●●●●	I/O Mirror

*Pyramex retail packaged product



vimeo.com/pyramex/h2max

There's more to see at
PYRAMEXSAFETY.COM
 (P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●), Australian (AS/NZS 1337) (●) or Ballistic (MIL-PRF-32432) (●) standards.

Venture 3[®]

General Specifications

Weight: 28 gm
 PD: 68 mm
 Bridge: 12.8 mm
 Lens base: 9.5 curve
 Lens size diagonal: 82 mm
 Lens size vertical: 46.6 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 150 - 163 mm
 Overall width (hinge - hinge): 139.4 mm
 Closest point between temple tips: 91 mm
 Closest point between lens: 13.1 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Sleeve: polycarbonate
 Nosepiece: bridge - polycarbonate and nose pad - polyvinyl chloride (PVC)
 Side shields: polycarbonate

Part No.	Lens Marking	Frame Marking
SB5710D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYSB5710D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5710DT	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5710DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720DT	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5730D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYSB5730D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5750SFT	P + W5	P Z87 +
SB5760D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5760SFT	P + W3	P Z87 +
SB5770D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5780D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose
 W: Welding filter
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

