



**Venture 3®** ANSI CE CSA AS BALLISTIC



VENTED FRAME



ADJUSTABLE NOSEPIECE



ADJUSTABLE TEMPLES



CO-INJECTED TEMPLES

Soft, adjustable nosepiece

Ventilated frame

Adjustable co-injected rubber temples

Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Part No.	Black Frame
SB5710D ●●●●	Clear
PYSB5710D* ●●●●	Clear
SB5710DT ●●●●	AF Clear H2X
SB5710DTM ●●●●	AF Clear H2MAX
SB5720D ●●●●	Gray
SB5720DT ●●●●	AF Gray H2X
SB5730D ●●●●	Amber
PYSB5730D* ●●●●	Amber
SB5760D ●●●●	Infinity Blue
SB5770D ●●●●	Silver Mirror
SB5780D ●●●●	I/O Mirror

\*Pyramex retail packaged product



[vimeo.com/pyramex/h2max](https://vimeo.com/pyramex/h2max)

There's more to see at  
**PYRAMEXSAFETY.COM**  
 (P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●), Australian (AS/NZS 1337) (●) or Ballistic (MIL-PRF-32432) (●) standards.

## Venture 3<sup>®</sup>

### General Specifications

Weight: 28 gm  
 PD: 68 mm  
 Bridge: 12.8 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 82 mm  
 Lens size vertical: 46.6 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 150 - 163 mm  
 Overall width (hinge - hinge): 139.4 mm  
 Closest point between temple tips: 91 mm  
 Closest point between lens: 13.1 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Sleeve: polycarbonate  
 Nosepiece: bridge - polycarbonate and nose pad - polyvinyl chloride (PVC)  
 Side shields: polycarbonate

Part No.	Lens Marking	Frame Marking
SB5710D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYSB5710D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5710DT	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5710DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720DT	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5730D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
PYSB5730D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5760D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5770D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5780D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special purpose  
 W: Welding filter  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

