

XS3®



Black Frame

Part Lens
SB4670S•  Silver Mirror

Realtree Hardwoods® HD™ Frame

Part Lens
SC4610S•  Clear

- Slim Temples for custom fit.
- Soft foam padding provides comfort fit.
- Open temples allow clip on cord option for goggle-like fit.
- Sports-look Safety Spectacle with superior eye protection.
- Unique temple design with co-injection temple tips for cushion comfort.
- Lenses are coated for superior scratch resistance, provide 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 19.3mm
Closest Point Between Temple Tips: 79mm
Lens Base: 7 Curve
Lens Size Diagonal: 131mm
Lens Size Vertical: 50mm
Lens Thickness: 2.1mm
Overall Length (Lens-Tip): 155mm
Overall Width (Hinge-Hinge): 147mm
PD: 68mm
Weight: 29g



PACKAGING

Polybag: 1 pc

Inner Box: 12 pcs

Outer Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	7 base curve, wrap around design with side protection
Frame	Nylon	Rounded frame with good coverage
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	Universal, integral to lens
Clip	Nylon	Snap the lens securely, with intelligent structure
Temple	Polycarbonate	Spatula with soft tip end
Temple Tip	TPE	Additionally co-injected with soft cushion tip
Hinge	Polycarbonate	3 barrel type
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB4670S	 Silver Mirror	P Z87 + S	P Z87 +
SC4610S	 Clear	P Z87 + U6	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

W: Welding Filter

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact