



PYRAMEX
Perform At Your Peak™

carhartt 

Billings® ANSI CSA



CO-INJECTED
TEMPLES

Lightweight, frameless design

Wrap-around coverage for superior protection

Available in a Carhartt clamshell or polybag

Clamshell Part No.	Lens and Temples	
CH110STCS ●●	AF	Clear
CH120STCS ●●	AF	Gray

Polybag Part No.	Lens and Temples	
CH110S ●●		Clear
CH110ST ●●	AF	Clear
CH118S ●●		Sandstone Bronze
CH120S ●●		Gray
CH120ST ●●	AF	Gray



Polybags



Clamshell

There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and Canadian (CSA Z94.3) (◉) standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.



PYRAMEX
Perform At Your Peak™



Billings®

General Specifications

Weight: 26 gm
 Lens base: 10 curve
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 130 mm
 Overall width (hinge - hinge): 137 + 1 mm
 Closest point between temple tips: 105 + 5 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Temple: polycarbonate
 Temple tips: thermoplastic rubbers (TPR)
 Screw: stainless steel

Part No.	Lens Marking	Temple Marking
CH110S	P	P Z87 + / P c SEI CAN/CSA Z94.3-15
CH110ST	P	P Z87 + / P c SEI CAN/CSA Z94.3-15
CH110STCS	P	P Z87 + / P c SEI CAN/CSA Z94.3-15
CH118S	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CH120S	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CH120ST	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CH120STCS	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967