






Shiny Black Frame

- | Part | Lens |
|---------------|---|
| VGSB1010DTB•• |  Clear Anti-Fog |
| VGSB1026DTB•• |  Forest Gray Anti-Fog |
| VGSB1057DTB•• |  Green Mirror Anti-Fog |

Camo Frame

- | Part | Lens |
|----------------|--|
| VGSCM1010DTB•• |  Clear Anti-Fog |
| VGSCM1018DTB•• |  Bronze Anti-Fog |
| VGSCM1026DTB•• |  Forest Gray Anti-Fog |







- Sporty, unisex design.
- Full wrap-around lens provides excellent impact protection.
- Vented foam padded frame provides superior comfort with great air flow.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Packaged in a Venture Gear branded polybag with retail tag.

GENERAL SPECIFICATION

Bridge: 19mm
Lens Base: 8 Curve
Lens Size Diagonal: 66.6mm
Lens Size Vertical: 34.7mm
Lens Thickness: 2mm
Overall Length (Lens-Tip): 118mm
Overall Width (Hinge-Hinge): 136.3mm
Weight: 36gm
PD: 64mm
Closest point between lenses: 19mm
Closest point between temple tips: 94mm

PACKAGING
Static sticker on bottom left lens
Temple tag with UPC code label
Sold individually in Venture Gear branded polybag
Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base dual lens
Frame	Polycarbonate	Foam padded frame
	EVA	
Nose Piece	TPR	Glued to frame
Temple	Polycarbonate	Co-injected rubber temples
	TPR	
Metal Emblem	Copper	Recessed on temples
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB1010DTB	 Clear Anti-Fog	P + U6	P Z87 +
VGSB1026DTB	 Forest Gray Anti-Fog	P + U6 L3	P Z87 +
VGSB1057DTB	 Green Mirror Anti-Fog	P + U6 L3	P Z87 +
VGSCM1010DTB	 Clear Anti-Fog	P + U6	P Z87 +
VGSCM1018DTB	 Bronze Anti-Fog	P + U6 L3	P Z87 +
VGSCM1026DTB	 Forest Gray Anti-Fog	P + U6 L3	P Z87 +

LENS MARKING

Symbols:

- P: Manufacturer's mark
- Z87: ANSI standard for Eye and Face protection devices
- +: High Impact
- H: Small Head Size
- S: Special Purpose

UV Filter Transmittance:

- U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
- U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
- U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
- U4: Max Effective Far UV= .04% / Max Near UV= .5%
- U5: Max Effective Far UV= .02% / Max Near UV= .2%
- U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

- L1.3: 85% Max. Visible Light
- L1.7: 55% Max. Visible Light
- L2.5: 29% Max. Visible Light
- L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

- P: Manufacturer's mark
- Z87: ANSI standard for Eye and Face protection devices
- +: High Impact
- P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices