


Cappture Pro ANSI • CE • CSA



Dielectric // Fits over most prescription glasses // Flexible rubber gasket // Full strap with quick release // Passes D3: Droplet and Splash Test // Passes D4: Dust Test

Rubber Gasket with Strap | 2 Variations

- GG9910TM ● ● Clear **H2MAX AF**
- GG9920TM ● ● Gray **H2MAX AF**



Part No.	Lens Marking	Temple Marking
GG9910TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3
GG9920TM	P Z87 + U6 L2.5X	P Z87 + D3 D4 / P c SEI Z94.3

General Specifications

Weight: 66.2 gm
 PD: 64 mm
 Bridge: 31 mm
 Lens base: 2.5 curve
 Lens size diagonal: 144 mm
 Lens size vertical: 52.2 mm
 Lens thickness: 2.0 mm
 Overall length: 92 mm
 Overall width: 178 mm

Materials

Lens: polycarbonate
 Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
 Nosepiece: polycarbonate
 Strap holder: nylon
 Headband: polyester & polyoxymethylene

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 X: Tested Anti-fog
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 D3: Droplet & Splash Test
 D4: Dust Test
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Visible Light Filters

L2.5: 29% max visible light