

Frameless Wraparound Safety Glasses

Easley™

ANSI CSA



Rubber Nosepiece



Adjustable Nosepiece



Anti-Fog



Ultraviolet Protection



Scratch Resistant

FEATURES

Built-in browguard

Adjustable nosepiece

Vented co-injected temples

MODEL NO. STYLE NO.

EE810 CHB810ST ● Clear Anti-fog

EE818 CHB818ST ● Sandstone Bronze Anti-fog

EE820 CHB820ST ● Gray Anti-fog

Available in a Carhartt polybag
Carhartt packaging design subject to change



Model No: EE820
Style No: CHB820ST



GENERAL SPECIFICATIONS

Weight: 31 gm

Bridge: 11.8 mm

Lens base: 9 curve

Lens size diagonal: 62.1 mm

Lens size vertical: 44.9 mm

Lens thickness: 2.2 mm

Overall length (lens - tip): 165.4 mm

Overall width (hinge - hinge): 144.1 mm

Closest point between temple tips: 93 mm

Closest point between lens: 11.8 mm

MATERIALS

Lens: polycarbonate (PC)

Foam: thermoplastic rubber (TPR)

Temple: polycarbonate (PC)

Temple tips: thermoplastic rubber (TPR)

Nose pad: polyvinyl chloride (PVC)

LENS + TEMPLE MARKING SYMBOLS

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special purpose

c SEI Z94.3: CAN/GSA standard for eye and face protection devices

MODEL NO.	STYLE NO.	LENS MARKING	TEMPLE MARKING
EE810	CHB810ST	P+	P Z87+ / P c SEI Z94.3
EE818	CHB818ST	P+S	P Z87+ / P c SEI Z94.3
EE820	CHB820ST	P+S	P Z87+ / P c SEI Z94.3