



**Ever-Lite®** ANSI CE CSA



RUBBER NOSEPIECE



CO-INJECTED TEMPLES

Soft nosepiece for snug fit

Slim co-injected temples

Lightweight spectacle – 22 gm



vimeo.com/pyramex/h2max

Part No.	Black Frame
SB8610D ●●●	Clear
SB8610DT ●●●	AF Clear H2X
SB8610DTM ●●●	AF Clear H2MAX
SB8620D ●●●	Gray
SB8620DT ●●●	AF Gray H2X
SB8620DTM ●●●	AF Gray H2MAX
SB8623D ●●●	Dark Gray
SB8623DT ●●●	AF Dark Gray H2X
SB8625DTM ●●●	AF Light Gray H2MAX

Part No.	Black Frame
SB8624D ●●●	Photochromic
SB8630D ●●●	Amber
SB8660D ●●●	Infinity Blue
SB8660DT ●●●	AF Infinity Blue H2X
SB8660DTM ●●●	AF Infinity Blue H2MAX
SB8665D ●●●	Ice Blue Mirror
SB8680D ●●●	I/O Mirror
SB8680DT ●●●	AF I/O Mirror

**!** Note: Photochromic lens changes from clear to dark, after exposed to direct UV light. Changes from dark to clear, after removed from UV light.



**Ever-Lite Readers** ANSI CSA



RUBBER NOSEPIECE



CO-INJECTED TEMPLES

Part No.	Black Frame
SB8610R15 ●●●	Clear +1.5 Mag
SB8610R20 ●●●	Clear +2.0 Mag
SB8610R25 ●●●	Clear +2.5 Mag
SB8610R30 ●●●	Clear +3.0 Mag
SB8620R15 ●●●	Gray +1.5 Mag
SB8620R20 ●●●	Gray +2.0 Mag
SB8620R25 ●●●	Gray +2.5 Mag

There's more to see at  
**PYRAMEXSAFETY.COM**  
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) and Canadian [CSA Z94.3] (●) standards.

## Ever-Lite®

### General Specifications

Weight: 22 gm  
 PD: 64 mm  
 Bridge: 11.2 mm  
 Lens base: 8 curve  
 Lens size diagonal: 79.6 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 134.3 mm  
 Closest point between temple tips: 70 mm  
 Closest point between lens: 11 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB8610D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8610DT	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8610DTM	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620DT	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8620DTM	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8623D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8623DT	P + S	P Z87 +
SB8625DTM	P + S	P Z87 +
SB8624D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8630D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8660D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8660DT	P + S	P Z87 +
SB8660DTM	P + S	P Z87 +
SB8665D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8680D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB8680DT	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special purpose  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

## Ever-Lite Readers

### General Specifications

Weight: 22 gm  
 PD: 64 mm  
 Bridge: 11.2 mm  
 Lens base: 8 curve  
 Lens size diagonal: 79.6 mm  
 Lens size vertical: 43.3 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 134.3 mm  
 Closest point between temple tips: 70 mm  
 Closest point between lens: 11 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
SB8610R15	P + U6	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R20	P + U6	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R25	P + U6	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8610R30	P + U6	+3.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R15	P + U6 L2.5	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R20	P + U6 L2.5	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
SB8620R25	P + U6 L2.5	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special purpose  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L2.5: 29% max visible light

### Frame Marking Symbols

+1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 +3.00: magnification of +3.0  
 P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 - 2: Rx  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

