

GL405C

Nylon | Polyurethane

ANSI/ISEA 105-2016 – CUT A3 | PUNCTURE 4 | ABRASION 4
EN388: 2016 – 4X42C

Polyurethane palm coating // 13 gauge nylon liner //
Touch sensitivity // Low particulate shed

GL405C S – 2XL

Suggested Applications

Cutting Applications // Automotive //
Glass Handling // Metal Work

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Liner: 13 Gauge Nylon
Cuff: Nylon

This product contains components that may be a potential risk to allergic reactions [latex in the wrist cuff]. Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4X42C

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

ANSI/ISEA 105-2016

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				



PU



Abrasion



Cut



Tear



Puncture



Product markings may vary. Refer to the product sheet for the most current test report results.

Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China