

## Gravex® ANSI •

Built-in nosepiece // Custom imprinting available

### Black Frame | 4 Variations

- SB8910S • Clear
- SB8910ST • Clear **H2X** AF
- SB8920S • Gray
- SB8980S • I/O Mirror



### MARKINGS

Part No.	Lens Marking	Temple Marking
SB8610D	P + U6	P Z87 +
SB8610DT	P + U6	P Z87 +
SB8620D	P + U6 L2.5	P Z87 +
SB8680D	P + U6 L1.7	P Z87 +

#### Lens Marking Symbols

P: Manufacturer's mark

+: High impact

#### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

#### Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

#### Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

### SPECIFICATIONS

#### General Specifications

Weight: 25 gm

PD: 68 mm

Bridge: 10.06 mm

Lens base: 9.5 curve

Lens size diagonal: 80 mm

Lens size vertical: 46.5 mm

Lens thickness: 2.3 mm

Overall length (lens - tip): 156 mm

Overall width (hinge - hinge): 138.2 mm

Closest point between temple tips: 72 mm

Closest point between lens: 14.1 mm

#### Materials

Lens: polycarbonate

Frame: nylon

Temples: nylon

Screw: stainless steel