


Highlander™ Plus ANSI • CE • CSA • Ballistic •



Removable indirect vented flame resistant foam carriage // Detachable strap // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

Black and Gray Frame | 5 Variations

- SBG5010DT ●●● Clear **H2X AF**
- SBG5020DT ●●● Gray **H2X AF**
- SBG5030DT ●●● Amber **H2X AF**
- SBG5055DT ●●● Sky Red Mirror AF
- SBG5080DT ●●● I/O Mirror AF

i Highlander Plus is partially foam padded which allows for airflow.



Part No.	Lens Marking	Temple Marking
SBG5010DT	P + U6	P Z87 + / P c SEI Z94.3
SBG5020DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG5030DT	P + U6	P Z87 + / P c SEI Z94.3
SBG5055DT	P + S	P Z87 + / P c SEI Z94.3
SBG5080DT	P + U6 L1.7	P Z87 + / P c SEI Z94.3

General Specifications

Weight: 36 gm
 PD: 68 mm
 Bridge: 9 mm
 Lens base: 8 curve
 Lens size diagonal: 68.4 mm
 Lens size vertical: 49 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 166 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temple tips: 80 mm
 Closest point between lens: 15.6 mm

Materials

Lens: polycarbonate
 Frame: nylon
 Temples: polycarbonate & nylon
 Hinge: polycarbonate & nylon
 Screw: stainless steel
 Nosepiece: polyvinyl chloride (PVC)
 Strap: polyester
 Strap holder: polyethylene (POM)

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special Purpose
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light