

# Intrepid® II

ANSI • CE • Ballistic •



Nosepiece flange eliminates pressure on bridge of nose by evenly distributing weight of glass // Flexible rubber temples provide pressure-free fit behind the ear // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

## Black Temples | 2 Variations

- SB8810S • • • Clear
- SB8820S • • • Gray



## MARKINGS

Part No.	Lens Marking	Temple Marking
SB8810S	P Z87 + U6	P Z87 +
SB8820S	P Z87 + U6 L2.5	P Z87 +

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

## SPECIFICATIONS

### General Specifications

Weight: 30 gm  
 PD: 68 mm  
 Bridge: 14.1 mm  
 Lens base: 6.5 curve  
 Lens size diagonal: 145.2 mm  
 Lens size vertical: 50.6 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 172 mm  
 Overall width (hinge - hinge): 136.4 mm  
 Closest point between temple tips: 83 mm

### Materials

Lens: polycarbonate  
 Nose Piece: polycarbonate + thermoplastic elastomers  
 Temples: polycarbonate + thermoplastic elastomers  
 Hinge: polycarbonate  
 Screw: stainless steel