

# IONIX™

LIGHTWEIGHT CONTEMPORARY FRAME



PART	LENS	PART	LENS
SB8110D****	Clear	SB8116D****	Sandstone Bronze
SB8110DT****	Clear (Anti-Fog)	SB8165D****	Ice Blue Mirror
SB8120D****	Gray	SB8170D****	Silver Mirror
SB8120DT****	Gray (Anti-Fog)	SB8180D****	Indoor/Outdoor Mirror

- Extreme style in safety eyewear, with clean lines and sports appeal.
- Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Built-in rubber nose piece provides all day comfort.
- Rubber temples tips keep eyewear secure for the active worker.
- Scratch-resistant polycarbonate lenses provides maximum vision protection, filter out 99.9% of harmful UV rays.

GENERAL SPECIFICATION
Bridge: 15mm
Closest Point Between Lens: 9mm
Closest Point Between Temple Tips: 92mm
Lens Base: 8 Curve
Lens Size Diagonal: 80mm
Lens Size Vertical: 40mm
Lens Thickness: 2.0mm
Overall Length (Lens-Tip): 125mm
Overall Width (Hinge-Hinge): 137mm
Weight: 26gm

**PACKAGING**









Polybag: 1 pc

Inner Box: 12 pcs

Case: 300 pcs

**IONIX™****LIGHTWEIGHT CONTEMPORARY FRAME**

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, wrap around design
Frame	Nylon	Lightweight frame
Temple tips	TPR	Comfortable fit
Nose Piece	TPR	N/A
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
<b>SB8110D</b>	 Clear	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8110DT</b>	 Clear (Anti-Fog)	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8120D</b>	 Gray	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8120DT</b>	 Gray (Anti-Fog)	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8116D</b>	 Sandstone Bronze	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8165D</b>	 Ice Blue Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8170D</b>	 Silver Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07
<b>SB8180D</b>	 Indoor/Outdoor Mirror	P +	P Z87 + / P c SEI CAN/CSA Z94.3-07

**LENS MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

**FRAME MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices