

Legacy® ANSI • CE • UKCA • CSA •

Integrated side shields provide additional protection
// Lightweight spectacle – 23 gm

Lens and Temples | 6 Variations

- ES10910S ●●●● Clear
- ES10910STM ●●●● Clear H2MAX AF
- ES10920S ●●●● Gray
- ES10920STM ●●●● Gray H2MAX AF
- ES10950SF ●●●● 5.0 IR Filter
- ES10960SF ●●●● 3.0 IR Filter



Measurements

Weight: 23 gm
PD: 64 mm
Bridge: 10.7 mm
Lens base: 6 curve
Lens size diagonal: 51.5 mm
Lens size vertical: 46 mm
Lens thickness: 2 mm
Overall length (lens - tip): 155 mm
Overall width (hinge - hinge): 136 mm
Closest point between temple tips: 98.3 mm
Closest point between lens: 20.3 mm

Materials

Lens: polycarbonate
Nosepiece: polycarbonate
Side Shield: polycarbonate
Temples: polycarbonate
Screw: stainless steel

Part No.

Part No.	Lens Marking	Temple Marking
ES10910S	2C-1.2 P 1FT CE	CE P EN166 FT UKCA
ES10910STM	2C-1.2 P 1FT KN CE	CE P EN166 FT UKCA
ES10920S	5-2.5 P 1FT CE	CE P EN166 FT UKCA
ES10920STM	5-2.5 P 1FT KN CE	CE P EN166 FT UKCA
ES10950SF	3 P 1F CE	CE P EN166 FT UKCA
ES10960SF	5 P 1F CE	CE P EN166 FT UKCA

Lens Marking

Temple Marking

Lens Marking Symbols

Code - field of use
2 or 3: UV filter
5 or 6: Solar filter

Colour Perception
C: Unimpaired colour perception

Protection Class
1.2 - 6: Degree of visible light filtration

Optical Class
1: High optical quality - no optical distortion

Mechanical Strength
F: Low energy impact, resists a 6 mm, .86 g at 45 m/s
T: Impact protection at extreme temperature conditions

Symbols
P: Manufacturer's mark
K: Resistance to surface damage by fine particles
N: Filter with anti-fog
CE: Certification of the European Union

Temple Marking Symbols

Symbols
CE: Certification for European Union
P: Manufacturer's mark
EN166: Standard for protective eyewear
UKCA: Certification for United Kingdom

Mechanical Strength
F: Low energy impact
T: Impact protection at extreme temperature conditions