

## Onix Plus ANSI • CE •



Co-injected temples // Adjustable rubber nosepiece  
 // Unique 3-angle adjustable flip lens // Outer lens  
 flips down for applications where IR lenses are needed  
 // Custom imprinting available

### Black Frame | 2 Variations

-  SB4950STP • • Clear with 5.0 IR **H2X** AF
-  SB4960STP • • Clear with 3.0 IR **H2X** AF



Part No.	Lens Marking	Temple Marking
SB8650SF	P + U6 / P+ W5	P Z87 +
SB8660SF	P + U6 / P+ W3	P Z87 +

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 W: Welding filter

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### General Specifications

Weight: 27 gm  
 PD: 68 mm  
 Bridge: 15 mm  
 Lens base: 8 curve  
 Lens size diagonal: 141 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 161 mm  
 Overall width (hinge - hinge): 128 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate & nylon  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: polycarbonate & thermoplastic elastomers (TPE)  
 Side shields: polycarbonate  
 Ratchets: nylon