

Onix® ANSI • CE • AS • Ballistic •



CO-INJECTED TEMPLES



ADJUSTABLE NOSEPIECE



RATCHETING TEMPLES

Ratcheting co-injected temples // Adjustable rubber nosepiece // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Black Frame | 5 Variations

- SB4910S ••• Clear
- PYSB4910S* ••• Clear
- SB4910ST ••• Clear **H2X AF**
- SB4920S ••• Gray
- SB4980S ••• I/O Mirror

Black and Green Frame | 1 Variation

- SGR4910ST •• Clear **H2X AF**



SGR49

Black and Pink Frame | 2 Variations

- SP4910S •• Clear
- PYSP4910S* •• Clear



SP49



*Pyramex retail packaged product

General Specifications

- Weight: 27 gm
- Bridge: 15 mm
- Lens base: 8 curve
- Lens size diagonal: 141 mm
- Lens size vertical: 45 mm
- Lens thickness: 2.2 mm
- Overall length (lens - tip): 161 mm
- Overall width (hinge - hinge): 128mm
- Closest point between temple tips: 68 mm

Lens Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- UV Filter Transmittance
- U6: .01% max effective far UV • .1% max near UV
- Visible Light Filters
- L1.7: 55% max visible light
- L2.5: 29% max visible light

Materials

- Lens: polycarbonate
- Temples: polycarbonate
- Hinge: polycarbonate
- Nosepiece: polycarbonate | Nosepad: TPE
- Screw: Stainless Steel
- Ratchets: Nylon
- Side Shields: polycarbonate

Frame Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- + : High impact

Part No.	Lens Marking	Frame Marking
SB4910S	P Z87 + U6	P Z87 +
PYSB4910S*	P Z87 + U6	P Z87 +
SB4910ST	P Z87 + U6	P Z87 +
SB4920S	P Z87 + U6 L2.5	P Z87 +
SB4980S	P Z87 + U6 L1.7	P Z87 +
SGR4910ST	P Z87 + U6	P Z87 +
SP4910S	P Z87 + U6	P Z87 +
PYSP4910S*	P Z87 + U6	P Z87 +

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards [•] and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] [•] Canadian [CSA Z94.3-15 [•] third-party certification] [•], or Ballistic [MIL-PRF-32432] [•] standards.