



**WATCH THE VIDEO**  
[Vimeo.com/Pyramex/H2MAX](https://vimeo.com/Pyramex/H2MAX)

## Proximity® ANSI • CE • CSA •



FOAM PADDING



CO-INJECTED TEMPLES

Removable flame resistant foam padding // Lightweight spectacle – 26.3gm // Slim co-injected temples



### Black Frame | 6 Variations

|  |               |                           |
|--|---------------|---------------------------|
|  | SB9310ST ●●●  | Clear <b>H2X</b> AF       |
|  | SB9310STM ●●● | Clear <b>H2MAX</b> AF     |
|  | SB9323ST ●●●  | Dark Gray <b>H2X</b> AF   |
|  | SB9323STM ●●● | Dark Gray <b>H2MAX</b> AF |
|  | SB9330ST ●●●  | Amber <b>H2X</b> AF       |
|  | SB9380ST ●●●  | I/O Mirror AF             |

### Black and Lime Frame | 2 Variations

|  |                |                           |
|--|----------------|---------------------------|
|  | SBL9310STM ●●● | Clear <b>H2MAX</b> AF     |
|  | SBL9323STM ●●● | Dark Gray <b>H2MAX</b> AF |

## MARKINGS

| Part No.   | Lens Marking    | Temple Marking          |
|------------|-----------------|-------------------------|
| SB9310ST   | P Z87 + U6      | P Z87 + / P c SEI Z94.3 |
| SB9310STM  | P Z87 + U6 X    | P Z87 + / P c SEI Z94.3 |
| SB9323ST   | P Z87 + S       | P Z87 + / P c SEI Z94.3 |
| SB9323STM  | P Z87 + S X     | P Z87 + / P c SEI Z94.3 |
| SB9330ST   | P Z87 + U6      | P Z87 + / P c SEI Z94.3 |
| SB9380ST   | P Z87 + U6 L1.7 | P Z87 + / P c SEI Z94.3 |
| SBL9310STM | P Z87 + U6 X    | P Z87 + / P c SEI Z94.3 |
| SBL9323STM | P Z87 + S X     | P Z87 + / P c SEI Z94.3 |

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special Purpose  
 X: Tested Anti-fog

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

## SPECIFICATIONS

### General Specifications

Weight: 26.3 gm  
 PD: 64 mm  
 Bridge: 16.5 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 75.8 mm  
 Lens size vertical: 50.4 mm  
 Lens thickness: 1.6 mm  
 Overall length (lens - tip): 161 mm  
 Overall width (hinge - hinge): 135 mm  
 Closest point between temple tips: 77 mm  
 Closest point between lens: 14.5 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Foam gasket: nylon & ethylene-vinyl acetate (EVA) foam