



**Sitecore™** ANSI • CE • CSA •



Built-in rubber nosepiece // Flexible and ventilated temples // Ratcheting temples // Temples adjust to three different lengths // Custom imprinting available

**Black and Gray Frame | 6 Variations**

- SBG10110D •• Clear
- SBG10110DTM •• Clear **H2MAX AF**
- SBG10120D •• Gray
- SBG10120DTM •• Gray **H2MAX AF**
- SBG10130D •• Amber
- SBG10180D •• I/O Mirror

**Gray and Lime Frame | 5 Variations**

- SGL10110D ••• Clear
- SGL10110DTM ••• Clear **H2MAX AF**
- SGL10120D ••• Gray
- SGL10120DTM ••• Gray **H2MAX AF**
- SGL10180D ••• I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SBG10110D	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 24.4 gm	Lens: polycarbonate
SBG10110DTM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Bridge: 10.6 mm	Frame: polycarbonate
SBG10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 8 curve	Nosepiece: thermoplastic rubber
SBG10120DTM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3	Lens size diagonal: 74 mm	Ratchet: polycarbonate
SBG10130D	P Z87 + U6	P Z87 + / P c SEI Z94.3	Lens size vertical: 41.5 mm	Sleeve: nylon
SBG10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Lens thickness: 2.2 mm	Temple: nylon
SGL10110D	P Z87 + U6	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 158 mm	Screw: stainless steel
SGL10110DTM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 132.5 mm	
SGL10120D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Closest point between temple tips: 55 mm	
SGL10120DTM	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3		
SGL10180D	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3		

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 X: Tested Anti-fog

**UV Filter Transmittance**

U6: .01% max effective far UV • .1% max near UV

**Visible Light Filters**

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices