

## Solo<sup>®</sup> ANSI • CE • CSA •

Temples are vented to reduce fogging // Custom imprinting available

### Lens and Temples | 4 Variations

- S510S   Clear
- S510SD   Clear Dispenser pack – 12 per box



#### General Specifications

Weight: 46 gm  
 Lens base: 4 curve  
 Lens size diagonal: 145 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2 mm  
 Overall length (lens - tip): 108 mm  
 Overall width (hinge - hinge): 159 mm

#### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate  
 Side Shield: polycarbonate  
 Hinge: polycarbonate  
 Nosepiece: polycarbonate

#### Part No.

S510S  
 S510SD

#### Lens Marking

P Z87+ U6  
 P Z87+ U6

#### Temple Marking

P Z87 + / P c SEI Z94.3  
 P Z87 + / P c SEI Z94.3

#### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV

#### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices