















## Venture II® ANSI • CE • CSA • Ballistic •



Temples adjust to four different lengths // Rubber nosepiece secures the glass and prevents slipping // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

### Black Frame | 14 Variations

 SB1810S ●●●● Clear	 SB1860SF ●●●● 3.0 IR Filter
 SB1810ST ●●●● Clear H2X AF	 SB1870S ●●●● Silver Mirror
 SB1820S ●●●● Gray	 SB1875S ●●●● Blue Mirror
 SB1820ST ●●●● Gray H2X AF	 SB1880S ●●●● I/O Mirror
 SB1830S ●●●● Amber	 SB1880ST ●●●● I/O Mirror AF
 SB1835S ●●●● Sun Block Bronze	 SB1890S ●●●● Gold Mirror
 SB1840S ●●●● Orange	
 SB1860S ●●●● Infinity Blue	


















## Venture II® Readers ANSI • CE • CSA •



Temples adjust to four different lengths // Rubber nosepiece secures the glass and prevents slipping // Custom imprinting available

### Black Frame | 15 Variations

 SB1810R10 ●●●● Clear +1.0 Mag	 SB1820R15 ●●●● Gray +1.5 Mag
 SB1810R15 ●●●● Clear +1.5 Mag	 SB1820R20 ●●●● Gray +2.0 Mag
 SB1810R15T ●●●● Clear H2X AF +1.5 Mag	 SB1820R25 ●●●● Gray +2.5 Mag
 SB1810R20 ●●●● Clear +2.0 Mag	 SB1820R30 ●●●● Gray +3.0 Mag
 SB1810R20T ●●●● Clear H2X AF +2.0 Mag	 SB1880R15 ●●●● I/O Mirror +1.5 Mag
 SB1810R25 ●●●● Clear +2.5 Mag	 SB1880R20 ●●●● I/O Mirror +2.0 Mag
 SB1810R25T ●●●● Clear H2X AF +2.5 Mag	 SB1880R25 ●●●● I/O Mirror +2.5 Mag
 SB1810R30 ●●●● Clear +3.0 Mag	



## Venture II®

### General Specifications

Weight: 27 gm  
 PD: 68 mm  
 Bridge: 10.5 mm  
 Lens base: 9.75 curve  
 Lens size diagonal: 56 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 150-163 mm  
 Overall width (hinge - hinge): 142 mm

### Materials

Lens: polycarbonate  
 Frame: nylon 6-6 - poly(hexamethylene adipamide)  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate + nylon  
 Screw: stainless steel  
 Side shields: polycarbonate  
 Nosepiece: polycarbonate + thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB1810S	P + U6	P Z87 + / P c SEI Z94.3
SB1810ST	P + U6	P Z87 + / P c SEI Z94.3
SB1820S	P + U6 L 2.5	P Z87 + / P c SEI Z94.3
SB1820ST	P + U6 L 2.5	P Z87 + / P c SEI Z94.3
SB1830S	P + U6	P Z87 + / P c SEI Z94.3
SB1835S	P + S	P Z87 + / P c SEI Z94.3
SB1840S	P + S	P Z87 + / P c SEI Z94.3
SB1860S	P + S	P Z87 + / P c SEI Z94.3
SB1860SF	P + W3	P Z87 + / P c SEI Z94.3
SB1870S	P + S	P Z87 + / P c SEI Z94.3
SB1875S	P + S	P Z87 + / P c SEI Z94.3
SB1880S	P + U6 L 1.7	P Z87 + / P c SEI Z94.3
SB1880ST	P + U6 L 1.7	P Z87 + / P c SEI Z94.3
SB1890S	P + S	P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special Purpose  
 W: Welding filter  
**UV Filter Transmittance**  
 U6: .01% max effective far UV • .1% max near UV  
**Visible Light Filters**  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

## Venture II Readers

### General Specifications

Weight: 27 gm  
 PD: 68 mm  
 Bridge: 10.5 mm  
 Lens base: 9.75 curve  
 Lens size diagonal: 56 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 150-163 mm  
 Overall width (hinge - hinge): 142 mm

### Materials

Lens: polycarbonate  
 Frame: nylon 6-6 - poly(hexamethylene adipamide)  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate + nylon  
 Screw: stainless steel  
 Side shields: polycarbonate  
 Nosepiece: polycarbonate + thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SB1810R10	P + U6	+1.00 P Z87 + / P c SEI Z94.3
SB1810R15	P + U6	+1.50 P Z87 + / P c SEI Z94.3
SB1810R15T	P + U6	+1.50 P Z87 + / P c SEI Z94.3
SB1810R20	P + U6	+2.00 P Z87 + / P c SEI Z94.3
SB1810R20T	P + U6	+2.00 P Z87 + / P c SEI Z94.3
SB1810R25	P + U6	+2.50 P Z87 + / P c SEI Z94.3
SB1810R25T	P + U6	+2.50 P Z87 + / P c SEI Z94.3
SB1810R30	P + U6	+3.00 P Z87 + / P c SEI Z94.3
SB1820R15	P + U6 L 2.5	+1.50 P Z87 + / P c SEI Z94.3
SB1820R20	P + U6 L 2.5	+2.00 P Z87 + / P c SEI Z94.3
SB1820R25	P + U6 L 2.5	+2.50 P Z87 + / P c SEI Z94.3
SB1820R30	P + U6 L 2.5	+3.00 P Z87 + / P c SEI Z94.3
SB1880R15	P + U6 L 1.7	+1.50 P Z87 + / P c SEI Z94.3
SB1880R20	P + U6 L 1.7	+2.00 P Z87 + / P c SEI Z94.3
SB1880R25	P + U6 L 1.7	+2.50 P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
**UV Filter Transmittance**  
 U6: .01% max effective far UV • .1% max near UV  
**Visible Light Filters**  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

+1.00: magnification of +1.0  
 +1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 +3.00: magnification of +3.0  
 P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices